## Single Jet Dry Dial Vane Wheel Water Meter

Model: LXSC-13D8S



#### **APPLICATION:**

Measuring the volume of cold potable water passing through the pipeline.

#### **FEATURES:**

- ◆ Single jet, dry dial;
- ◆ Magnetic drive, magnet resistance;
- Optimum accuracy and performance at all times;
- ◆ Accurate measurement, easy and long term clear reading, etc.

### **WORKING CONDITION:**

◆Water temperature: Cold Water Meter ≤40°C Hot Water Meter ≤90°C

◆Water pressure: ≤1.6Mpa (16bar)


#### **MAXIMUM PERMISSIBLE ERROR:**


♦ In the lower zone from  $q_{\min}$  inclusive up to but excluding  $q_t$  is ±5%

lacktriangle In the upper zone from q inclusive up to and including q is ±2%

Туре	Size (mm)	Class	q <sub>s</sub> Max.Flow	q <sub>p</sub> Nominal Flow	qt Transitional Flow	q <sub>min</sub> Min. Flow	Min.Reading	Max.Readin
			m³/h		L/h		m <sup>3</sup>	
LXSC-13D8S	15	В	3	1.5	120	30	0.0001	99999
		С			22.5	15		

Туре	Size	L	В	В	Connection Thread	Weight
LXSC-13D8	15	115	77	85	G3/4B	0.45kg





# 水头损失曲线 Pressure Loss Curve

