

MULTI-JET LIQUID-SEALED TYPE VANE WHEEL WATER METER

MODEL: LXSJ-15S-50S



APPLICATION

Measuring the volume of cold potable water passing through the pipeline

FEATURES

Adopting pointer and word-wheel combination count device, with advanced, beautiful and elegant structure, the counter is sealed by special type liquid, the reading is clear for long, convenient meter copy and long service life.

Class C water meter is available for 15mm (1/2 inch) and 20mm (3/4 inch).

WORKING CONDITION

Water temperature: $\leq 50^{\circ}\text{C}$ for cold water meter

$\leq 90^{\circ}\text{C}$ for hot water meter

Water pressure: $\leq 1\text{MPa}$ or 1.6MPa optional

(10bar or 16bar optional)

MAXIMUM PERMISSIBLE ERROR

In the lower zone from $Q_{\min}$ inclusive up to but excluding Q_t is $\pm 5\%$ _ In the upper zone from Q_t

inclusive up to and including Q_s is: cold water meter $\pm 2\%$, hot water meter $\pm 3\%$.

NOTE

Technical data conform to International Standard ISO4064

NINGBO AIMEI METER MANUFACTURE CO., LTD.

Address: 68 Western Town Road Shangtian Town Fenghua City Zhejiang China-315511

Tel: +86-574-88637838

Fax: +86-574-88637968

Email: [aime@chinaaime.com](mailto:aimei@chinaaime.com)

MAIN TECHNICAL DATA

Type	Size (mm)	Class	Qn Max. Flow	Qp Nominal Flow	Qn Transitional Flow	Qmin Min. Flow	Min. Reading	Max. Reading
			M ³ /h		L/h		M ³	
LXSY-15S	15	A	3	1.5	150	60	0.0001	99999
		B			120	30		
		C			22.5	15		
LXSY-20S	20	A	5	2.5	250	100	0.0001	99999
		B			200	50		
		C			37.4	25		
LXSY-25S	25	A	7	3.5	350	140	0.0001	99999
		B			280	70		
LXSY-32S	32	A	12	6.0	600	240	0.0001	99999
		B			480	120		
LXSY-40S	40	A	20	10	1000	400	0.001	99999
		B			800	200		
LXSY-50S	50	A	30	15	1500	600	0.001	99999
		B			1200	300		

ACCESSORIES

Each water meter has one set couplings optional: 2pcs tube, 2pcs nut and 2pcs gasket.

DIMENSIONS AND WEIGHT

Type	Size	Length	Width	Height	Connecting Thread D	Weight (kg)
mm						
LXSY-15S	15	165/190	99	104	G 3/4B	1.4/1.6
LXSY-20S	20	190/195	99	106	G 1B	1.7/1.8
LXSY-25S	25	260/225	103	114	G1 1/4B	2.6/2.4
LXSY-32S	32	260/230	104	117	G1 1/2B	2.8/2.7
LXSY-40S	40	300/245	124	147	G 2B	5.1/4.5
LXSY-50S	50	300/280	125	172	G2 1/2B	8.5/8.2
					Flange connect GB4216.4-84 D=165 D1= 125	11.5/11

NINGBO AIMEI METER MANUFACTURE CO., LTD.


Address: 68 Western Town Road Shangtian Town Fenghua City Zhejiang China-315511

Tel: +86-574-88637838


Fax: +86-574-88637968

Email: aimei@chinaaimei.com

FLOW ERROR CURVE



PRESSURE LOSS CURVE



NINGBO AIMEI METER MANUFACTURE CO., LTD.

Address: 68 Western Town Road Shangtian Town Fenghua City Zhejiang China-315511

Tel: +86-574-88637838

Fax: +86-574-88637968

Email: aimei@chinaaimei.com